

# NetWay5B

5-Port Hardened Switch

Rev. 08112022



Netua

NetWay5B

<ul> <li>Specifications — Input Power</li> </ul>	PoE (53.5V), current draw: 1.8W 12VDC, current draw: 150mA 24VDC, current draw: 75mA	Physical and Environmental Dimensions (L x W x H) Board: 5.6" x 3.55" x 0.75" (142.2mm x 90mm x 19mm)	
Output	Five (5) data ports	Shipping: 8" x 6" x 5" (203.2mm x 152.4mm x 127mm)	
Ethernet Ports:	Five (5) 10/100/1000 Mbps ports Connectivity: RJ45, auto-crossover Wire type: 4-pair CAT5 or better structured cable Distance: up to 100m Speed: 10/100/1000 Mbps, half/full duplex, auto negotiation	Weight (approx.)Product Weight:Shipping Weight:TemperatureOperating:Storage:Relative HumidityOperating Altitude	0.25 lb. (0.11 kg) 0.75 lb. (0.34 kg) - 30°C to 70°C (- 22°F to 158°F) - 40°C to 85°C (- 40°F to 185°F) 85% +/- 5% e: - 304.8 to 2,000m
Indicators (LED)		Mounting hardware included	
Individual PoE On LED	1		
Individual IP Link status, 10/100Base-T/active LEDs for each port			

Altronix Netway5B is a space-saving hardened switch board that mounts easily inside of Altronix enclosures, improving installation efficiency. It is an ideal solution in all Maximal and Trove series products, allowing for the connection of up to 4 IP devices within the enclosure

- utilizing a single Ethernet cable going to the headend.

### Accessories (order separately)



#### **BR1 – Mounting Bracket**

Add-on mounting bracket compatible with Altronix Maximal and Trove enclosures. Allows to mount one (1) NetWya5A, NetWay5B, PD4UL(CB), PD8UL(CB), ACM4(CB), MOM5, VR6, PDS8(CB) or LINQ8PD(CB) sub-assembly on the enclosure's wall, saving valuable space.

BR1 with sub-assmebly (not included) mounted to side wall of Trove Enclosure.

# NetWay5B

5-Port Hardened Switch

### - Dimensions and Drawing -

Board Dimensions (L x W x H approximate)

5.6" x 3.55" x 0.75" (142.2mm x 90mm x 19mm)

Mounting Holes' Tolerance: +/- 0.04 in. (1mm)



